



ULTRA SOLDERING TOOLS

ULSOOLS

TECHNICAL DATA SHEET

LIQUID FLUX - UST 101

highly activated, water-soluble

DESCRIPTION

Ulsools Ust101 liquid flux is water based and water-soluble liquid flux that becomes highly activated at soldering temperatures. Post-soldering flux residues must be cleaned, but are easily removed with water.

APPLICATION

Ulsools Ust 101 liquid flux is a highly activated flux used for soldering operations on very oxidized Pcb , wire, cable, and other Electrical parts.

Ust 101 fluxes have a high solid content, The high activity of water-soluble fluxes gives them excellent soldering performance.

PHYSICAL PROPERTIES AND DATA

GENERAL PROPERTIES	LIQUID FLUX UST 101
Colour:	Pale goldenrod
PH value:	5 - 6
Thinner:	water
Packing:	500 CC-1000 CC-3 LITRE-20 LITRE

SHELF LIFE

3 years after date of Production (provided proper storage in originally sealed container)

HEALTH AND SAFETY

Before Using please read the material safety data sheet carefully and observe the safety precautions described.

NOTICE

The above values are Typical And represent no form of specification . The Data Sheet Serves for information purposes.

ULSOOLS CO · TDS UST101_EN

TEL:+989384244289

E-MAIL:ULTRASOLDERINGTOOLS@GMAIL.COM

WEBSITE:WWW.ULSOOLS.COM