



ULTRA SOLDERING TOOLS

ULSOOLS

TECHNICAL DATA SHEET

## LIQUID FLUX - UST 114

no-clean, halide free flux, low solid

### DESCRIPTION

---

Ust 114 liquid flux is a Isopropanol based halogen-free organic liquid solder flux with low activity. It is a no-clean flux with a low solids content that leaves virtually no residue. Solder joints appear shiny after soldering, even without cleaning.

### APPLICATION

---

Ulsools Ust 114 liquid flux is the best soldering flux for wave soldering and surface mount assembly.

This halogen free soldering flux can be used in both automated and manual soldering applications and Can be used with both lead-free and leaded alloys.

### PHYSICAL PROPERTIES AND DATA

---

GENERAL PROPERTIES	LIQUID FLUX UST 114
Colour:	colourless liquid
PH value:	7
Solder Alloy:	lead-free & leaded
Packing:	500 CC-1000 CC-3 LITRE-20 LITRE

### SHELF LIFE

---

2 years after date of Production (provided proper storage in originally sealed container)

### HEALTH AND SAFETY

---

Before using please read the material safety data sheet carefully and observe the safety precautions described.

### NOTICE

---

The above values are typical and represent no form of specification . The Data Sheet serves for information purposes.

---

ULSOOLS CO · TDS UST 114\_EN

TEL:+989384244289

E-MAIL:ULTRA SOLDERING TOOLS@GMAIL.COM

WEBSITE:WWW.ULSOOLS.COM